WASH & **WAX SHAMPOO**





SAFETY DATA SHEET AVAILABLE ON REQUEST

Always refer to the descriptions on labels. Keep out of reach of children. Respect the conditions of use.

Description

- Concentrated formula with waxing agents, the 205W allows regular cleaning of hulls and superstructures while depositing a water repellent film that provides a glossy finish.
- Without phosphates.
- Marpol Annex 5 compliant.

Product information

Composition	Sodium salts of sulfonic acid base. Anionic surfactants 15-30% Preservatives (Methylchloroisothiazolinone, Methylisothiazolinone), perfume
Appearance/ Odour	Opaque liquid / apple
рН	8
Density	1.01 à 20°C (68°F)
Flash point	N.A
Transport N° ONU	N.A
Storage	Store product in original packaging. Close tight. Temperature: + 5 ° C to + 50 ° C
Packaging	1L / 5L

Directions for use

Compatibility / supports	Gelcoat, painted and varnished surfaces, sails, awnings, etc.
Méthodes	- Dilute 3 to 7% product in water.
	- Wet the surface and apply the mixture with a soft brush.
	- Leave for a few minutes then rinse thoroughly with clear water.

Precautions for use

• Causes skin irritation. Causes serious eye damage. Before use: Always perform a test on a small surface. Do not use in direct sunlight.

