

# 31

## RUST CONVERTER

### Description

- Anti-corrosion formulation, 31 converts the rust into a protective barrier (organo-metallic compound) on all ferrous metals. It is perfectly suited for both uses, protecting parts exposed to oxidation and as a primer before painting.

### Product information

<b>Composition</b>	Vinyl acrylate copolymer in aqueous phase, ethylene glycol.
<b>Appearance/ Odour</b>	Liquid / characteristic
<b>pH</b>	2.4
<b>Density</b>	1.11+/-0.03
<b>Flash point</b>	>70°C (>158°F)
<b>Transport N° ONU</b>	1805
<b>Storage</b>	Store in the original package. Keep container closed tightly.
<b>Packaging</b>	250ml / 1L / 5L



### Directions for use

<b>Compatibility / supports</b>	metals
<b>Méthodes</b>	<ul style="list-style-type: none"> <li>- The part to be treated should be brushed, degreased and free of mildew, rinsed with clean water and kept moist to assure the penetration into the rust.</li> <li>- 31 is used pure, with a brush, spray or by dipping.</li> <li>- Leave to dry 12 to 24 hours before painting. NB. A second coat may be needed for any very deep corrosion.</li> <li>- A paint coat is recommended, in the month following treatment, to insure the duration of effectiveness of 31.</li> </ul>

**SAFETY DATA SHEET  
AVAILABLE ON REQUEST**

Always refer to the descriptions on labels. Keep out of reach of children. Respect the conditions of use.

### Precautions for use

- Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.  
Before use: Always carry out a test on a small area.



**Warning**